

864 Text Message

Functional Group ID= **TX**

Introduction:

This Draft Standard for Trial Use contains the format and establishes the data content of the Text Message Transaction Set (864) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide users with a capability to electronically move messages, contracts, explanations, and other one-time communications. It is the intent of this transaction set to provide electronic communication (messages) for people, not for computer processing. The use of the transaction set to transmit quasi or unique transaction set standards is discouraged. The use of the Text Message transaction set demands of the sender certain detailed information about the recipient. The transaction set's purpose is to provide communication to the recipient in some human-readable form. The recipient's network will dictate what capabilities are available for delivery of the information. It is the responsibility of the sender to obtain this information and include it in the transmission.

Heading:

<u>Page No.</u>	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
3	010	ST	Transaction Set Header	M	1		
4	020	BMG	Beginning Segment For Text Message	M	1		
5	030	DTM	Date/Time Reference	O	10		
LOOP ID - N1						200	
Not Used	040	N1	Name	O	1		
Not Used	050	N2	Additional Name Information	O	2		
Not Used	060	N3	Address Information	O	2		
Not Used	070	N4	Geographic Location	O	1		
Not Used	080	REF	Reference Identification	O	12		
Not Used	090	PER	Administrative Communications Contact	O	3		

Detail:

<u>Page No.</u>	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
LOOP ID - MIT						>1	
6	010	MIT	Message Identification	M	1		
LOOP ID - N1						200	
Not Used	020	N1	Name	O	1		
Not Used	030	N2	Additional Name Information	O	2		
Not Used	040	N3	Address Information	O	2		
Not Used	050	N4	Geographic Location	O	1		
Not Used	060	REF	Reference Identification	O	12		
Not Used	070	PER	Administrative Communications Contact	O	3		
7	080	MSG	Message Text	M	100000		

Summary:

<u>Page No.</u>	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
8	010	SE	Transaction Set Trailer	M	1		

Segment: **ST** Transaction Set Header
Position: 010
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Syntax Notes:
Semantic Notes: 1 The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
Comments:

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u> <u>Name</u>	
M	ST01	143 Transaction Set Identifier Code Code uniquely identifying a Transaction Set 864 Text Message	M ID 3/3
M	ST02	329 Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M AN 4/9

Segment: **BMG** Beginning Segment For Text Message
Position: 020
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the beginning of a Text Message Transaction Set
Syntax Notes:
Semantic Notes:
Comments: 1 BMG02 contains the message subject.

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element Name</u>	
M	BMG01	353 Transaction Set Purpose Code Code identifying purpose of transaction set 00 Original	M ID 2/2
	BMG02	352 Description A free-form description to clarify the related data elements and their content	O AN 1/80
Must Use	BMG03	640 Transaction Type Code Code specifying the type of transaction 65 Award Notification ME Memorandum	O ID 2/2

Segment: **DTM** **Date/Time Reference**
Position: 030
Loop:
Level: Heading
Usage: Optional
Max Use: 10
Purpose: To specify pertinent dates and times
Syntax Notes:

- 1 At least one of DTM02 DTM03 or DTM05 is required.
- 2 If DTM04 is present, then DTM03 is required.
- 3 If either DTM05 or DTM06 is present, then the other is required.

Semantic Notes:
Comments:

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element Name</u>	
M	DTM01	374 Date/Time Qualifier	M ID 3/3
		Code specifying type of date or time, or both date and time	
		164 First Issue	
		170 Supplemental Issue	
	DTM02	373 Date	X DT 8/8
		Date expressed as CCYYMMDD	
Not Used	DTM03	337 Time	X TM 4/8
		Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	
Not Used	DTM04	623 Time Code	O ID 2/2
		Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow	
		Refer to 004010 Data Element Dictionary for acceptable code values.	
Not Used	DTM05	1250 Date Time Period Format Qualifier	X ID 2/3
		Code indicating the date format, time format, or date and time format	
		Refer to 004010 Data Element Dictionary for acceptable code values.	
Not Used	DTM06	1251 Date Time Period	X AN 1/35
		Expression of a date, a time, or range of dates, times or dates and times	

Segment: **MIT** Message Identification
Position: 010
Loop: MIT Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To identify the beginning of a specific message and to allow the identification of a subject for the message

Syntax Notes:

Semantic Notes: 1 MIT01 contains the message number.
 2 MIT02 contains the message subject.

Comments: 1 MIT03 default is 80 characters.
 2 MIT04 default is 66 lines.

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u> <u>Name</u>	
M	MIT01	127 Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	M AN 1/30
Not Used	MIT02	352 Description A free-form description to clarify the related data elements and their content	O AN 1/80
Not Used	MIT03	931 Page Width Definition of the maximum number of characters per line that can be expected in the message text	O N0 1/3
Not Used	MIT04	932 Page Length Lines Definition of the maximum number of lines per page that can be expected in the message text	O N0 1/3

Segment: **MSG** Message Text
Position: 080
Loop: MIT Mandatory
Level: Detail
Usage: Mandatory
Max Use: 100000
Purpose: To provide a free-form format that allows the transmission of text information
Syntax Notes: 1 If MSG03 is present, then MSG02 is required.
Semantic Notes: 1 MSG03 is the number of lines to advance before printing.
Comments: 1 MSG02 is not related to the specific characteristics of a printer, but identifies top of page, advance a line, etc.
 2 If MSG02 is "AA - Advance the specified number of lines before print" then MSG03 is required.

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u> <u>Name</u>	
M	MSG01	933 Free-Form Message Text Free-form message text	M AN 1/264
	MSG02	934 Printer Carriage Control Code A field to be used for the control of the line feed of the receiving printer AT Advanced Three Lines Before Print DS Advance two lines before print NP Advance to next page before print NS No advance before print SS Advance to new line before print	X ID 2/2
Not Used	MSG03	1470 Number A generic number	O N0 1/9

Segment: **SE** Transaction Set Trailer
Position: 010
Loop:
Level: Summary
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Syntax Notes:

Semantic Notes:

Comments: 1 SE is the last segment of each transaction set.

Data Element Summary

	Ref.	Data		Attributes
		<u>Des.</u>	<u>Element</u> <u>Name</u>	
M	SE01	96	Number of Included Segments	M N0 1/10
			Total number of segments included in a transaction set including ST and SE segments	
M	SE02	329	Transaction Set Control Number	M AN 4/9
			Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	